

Workhorse laser printer that outputs in A3 at ultra fast speed.



Key Selling Features

- A4/A3 Monochrome Laser Beam Printer
- Up to 25 A4 pages per minute, and 18 A3 pages per minute
- Fast 10 second first print speed*
- Wide variety of network and software driver options

Short Description

In its standard configuration the Canon LBP-3500 delivers ultra high-speed, high-quality printing for workgroups using Windows. Offering print speeds of up to 25 ppm, and resolution up to 2400 x 600 dpi (AIR Equiv.), and standard print sizes up to A3, the LBP-3500 is the ultimate choice for any office environment. The LBP3500 can also be expanded with an extensive range of optional accessories.

Faster Than The Average

Print at up to 25 pages per minute A4, and up to 18 pages per minute A3

Connectivity And Expandability

- Windows CAPT (Canon Advanced Printing Technology) printing software as standard
- Standard 8MB memory, memory upgrades not required
- USB interface standard

Flexible Paper Handling

- Accepts all standard paper sizes from A5 to A3 plus a wide range of envelopes
- High 250 sheet capacity with paper cassette and 100 page multi-purpose tray included as standard
- Additional (optional) 500-sheet paper cassette can be added for a maximum capacity of 850 sheets

Optional Accessories

- 250 sheet Universal Cassette UC-67
- 500 sheet Optional Cassette UC-67k
- 500 sheet Paper Feeder Unit PF-67
- Duplex Unit DU-67

^{*} Based on A4 printing

LBP-3500 Specifications

General

Print Speed 25 ppm (A4/LTR), 18 ppm (A3)

Resolution 600 x 600 dpi

Smoothing Technology Automatic Image Refinement, (2400 dpi Equivalent x 600 dpi)

Printer Language CAPT (for Windows)

Warm Up Time In Standby: 15 seconds or less (switching from sleep to standby modes)

At power-on: 17 seconds or less

First Print Time 10 seconds (A4) or less

Paper Size Cassette: A3, B4, A4, B5, 11x17", LGL, LTR, Exec.

MP Tray: Custom paper size setting; User defined minimum width 98.0mm x length

148mm, (max.) width 312mm x length 470mm)

Paper Input Standard: MP Tray: 100 Sheets

Cassette: 250 Sheets

Optional: Paper feeder unit PF-67: 500 sheets (maximum capacity 850 sheets)

Paper Output 250 sheets

Power Requirements AC 220-240V (50H/60Hz)

Power Consumption Printing: Approx. 434W, Standby: Approx. 36W, Sleep mode: Approx. 7W

Dimensions 518 x 439 x 277mm (WxDxH)

Weight Approx. 19.3kg (excluding toner cartridge)

Toner Cartridge CART 309 Cartridge (Approx. 12,000 A4 pages @5% page coverage). Shipped with

CART309 starter cartridge 6,000 yield

CPU N/A

Interface Standard: USB 2.0

Optional: 10BASE-T/100Base-TX Ethernet Board NB-C1

Operating Platforms Windows ® 98, Windows ® Me and Windows ® 2000, 2003 and Windows ® XP.

1. Print speed may vary with the content and the processing speed of the host computer.

2. All data based on Canon's Standard Test Method.

3. Subject to change without notice.

